

SCHÜCO ADS 65 HD Door

Benefits

High thermal insulation variants

Optimized for heavy loads and usage

Burglar resistant - High security standards

Wide range of design variations

Technical Specifications

SCHÜCO ADS 65 HD Door – Performance EU Units

Energy	
Thermal Insulation – U_f	1.4 W/m ² K
Comfort	
Air tightness	Class 4
Water tightness	Class 7A
Acoustics – R_w	43 dB
Wind load resistance	Class C3
Safety	
Burglar resistance	RC2, RC3

Info.

SCHÜCO ADS 65 HD Door

Performance USA Units

Energy	
Thermal Insulation – U_f	0.25 Btu/hr.ft ² .°F
Comfort	
Air tightness	Class 4
Water tightness	Class 7A
Acoustics – R_w	43 dB
Wind load resistance	Class C3
Safety	
Burglar resistance	RC2, RC3

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259

SCHÜCO ADS 65 HD Door

Properties EU Units

Sightlines & Weight			
Max. height of vent	3000 mm	Min. face width	147 mm
Max. width of vent	1400 mm	Basic depth of outer frame	65 mm
Max. vent weight	200 kg	Basic depth of vent frame	65 mm
Glazing			
Min. glass thickness - vent	4 mm	Max. glass thickness - vent	45 mm

SCHÜCO ADS 65 HD Door

Properties USA Units

Sightlines & Weight			
Max. height of vent	118 1/8 inch	Min. face width	5 13/16 inch
Max. width of vent	55 1/8 inch	Basic depth of outer frame	2 9/16 inch
Max. vent weight	441 lbs	Basic depth of vent frame	2 9/16 inch
Glazing			
Min. glass thickness - vent	3/16 inch	Max. glass thickness - vent	1 3/4 inch

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259