

SCHÜCO ADS 70 HD Door

Benefits

High thermal insulation variants

Optimized for heavy loads and usage

Burglar resistant - High security standards

Wide range of design variations

Technical Specifications

SCHÜCO ADS 70 HD Door – Performance EU Units

Energy	
Thermal Insulation – U_f	1.4 W/m ² K
Comfort	
Air tightness	Class 2
Water tightness	Class 5A
Acoustics – R_w	43 dB
Wind load resistance	Class C3
Safety	
Burglar resistance	RC2, RC3

Info.

SCHÜCO ADS 70 HD Door

Performance USA Units

Energy	
Thermal Insulation – U_f	0.25 Btu/hr.ft ² .°F
Comfort	
Air tightness	Class 4
Water tightness	7.5 psf /Class 7A
Acoustics – R_w	43 dB
AAMA rating	CW
PG rating	50
Wind load resistance	Class C3
Safety	
Burglar resistance	RC2, RC3

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259

SCHÜCO ADS 70 HD Door

Properties EU Units

Sightlines & Weight			
Max. height of vent	3000 mm	Min. face width	147 mm
Max. width of vent	1400 mm	Max. vent weight	200 kg
Glazing			
Min. glass thickness - vent	6 mm	Max. glass thickness - vent	52 mm

SCHÜCO ADS 70 HD Door

Properties USA Units

Sightlines & Weight			
Max. height of vent	118 1/8 inch	Min. face width	5 13/16 inch
Max. width of vent	55 1/8 inch	Max. vent weight	441 lbs
Glazing			
Min. glass thickness - vent	1/4 inch	Max. glass thickness - vent	2 1/16 inch

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259