

## SCHÜCO ADS 75 HD.HI Door

### Benefits

High thermal insulation variants

Optimized for heavy loads and usage

Burglar resistant - High security standards

Wide range of design variations

### Technical Specifications

#### SCHÜCO ADS 75 HD.HI Door – Performance EU Units

<b>Energy</b>	
Thermal Insulation – $U_f$	1.4 W/m <sup>2</sup> K
<b>Comfort</b>	
Air tightness	Class 2
Water tightness	Class 5A
Acoustics – $R_w$	43 dB
Wind load resistance	Class C3
<b>Safety</b>	
Burglar resistance	RC2, RC3

#### Info.

# SCHÜCO ADS 75 HD.HI Door

## Performance USA Units

<b>Energy</b>	
Thermal Insulation – $U_f$	0.25 W/m <sup>2</sup> K
<b>Comfort</b>	
Air tightness	Class 2
Water tightness	7.5 psf / Class 5A
Acoustics – $R_w$	43 dB
AAMA rating	CW
PG rating	50
Wind load resistance	Class C3
<b>Safety</b>	
Burglar resistance	RC2, RC3

### Info.

# SCHÜCO ADS 75 HD.HI Door

## Properties EU Units

<b>Sightlines &amp; Weight</b>			
Max. height of vent	3000 mm	Min. face width	147 mm
Max. width of vent	1400 mm	Max. vent weight	200 kg
<b>Glazing</b>			
Min. glass thickness - vent	10 mm	Max. glass thickness - vent	57 mm

# SCHÜCO ADS 75 HD.HI Door

## Properties USA Units

<b>Sightlines &amp; Weight</b>			
Max. height of vent	118 1/8 inch	Min. face width	5 13/16 inch
Max. width of vent	55 1/8 inch	Max. vent weight	441 lbs
<b>Glazing</b>			
Min. glass thickness - vent	3/8 inch	Max. glass thickness - vent	2 1/4 inch

### Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: [www.simpasus.com](http://www.simpasus.com) // [info@simpas.gr](mailto:info@simpas.gr) - Phone: +30 26510 92177 // +30 697 668 9259