

OS2 75 AS

European Metric System - OS2 75 AS

Technical		2-Rail	
Visible	Frame	Min	25 mm
		Max	47 mm
	Vent	Min	47 mm
		Max	47 mm
	Chicane	Standard	
		49 mm	
Glazing Thickness		Up to 51 mm	
Interlock Vent-Vent		Min	125 mm
		Max	
Maximum Sash Weight		Manual	
		250 kg	
Vent Dimensions	Width	Min	850 mm
		Max	1560 mm
	Height	Min	1135 mm
		Max	3408 mm

Info.

American Metric System

OS2 75 AS

Technical		2-Rail	
Visible	Frame	Min	1 inch
		Max	1 7/8 inch
	Vent	Min	1 7/8 inch
		Max	1 7/8 inch
	Chicane	Standard	
		1 15/16 inch	
Glazing Thickness		Up to 2 inches	
Interlock Vent-Vent		Min	4 15/16 inch
		Max	
Maximum Sash Weight		Manual	
		550 lbs	
Vent Dimensions	Width	Min	34 inches
		Max	61 inches
	Height	Min	45 inches
		Max	134 inches

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259

European Metric System

OS2 75 AS

Performance	2 – rail
Thermal Insulation (W/m²·K) (EN ISO 10077-2)	Up to 1.0
Wind Load Resistance (DIN EN 12210)	Up to Class C3
Acoustic Performance (R_w) (DIN 52210)	-
Air Permeability (DIN EN 12207)	Up to Class 4
Water Tightness (DIN EN 12208)	Up to 5A Class

American Metric System

OS2 75 AS

Performance	2 - rail
Thermal Insulation (Btu/h·ft²·F) (EN ISO 10077-2)	Up to 0.18
Wind Load Resistance (DIN EN 12210)	Up to Class C3
Acoustic Performance (R_w) (DIN 52210)	-
Air Permeability (DIN EN 12207)	Up to Class 4
Water Tightness (DIN EN 12208)	Up to 5A Class

Info.

Address: Ampelia, Ioannina 45 500 Greece. - Web: www.simpasus.com // info@simpas.gr - Phone: +30 26510 92177 // +30 697 668 9259