

# Unico Standard

FRAME YOUR IDEAS WITH **ForsterWindows**

## CONTACT INFO

Simpas Live Better  
Location: Ampelia, Ioannina 45 500 Greece  
Phone: +30 26510 92177 // +30 697 668 9259  
www.simpasus.com

## Technical Details

Thermal Insulation:  $U_f = 1.5 \text{ W/m}^2\text{K}$

Acoustics:  $R_w(C;Ctr) : 47\text{dB}$

Min. frame width: Min. 30 mm

### Performance

#### Energy

Thermal insulation - $U_f$ :  $1.5 \text{ W/m}^2\text{K}$

#### Comfort

Air-Water-Wind: Class 4 (600Pa) -Class E1050 (1050Pa) -Class C5 (2000Pa)

Acoustics - $R_w(C;Ctr) : 47 \text{ dB}$

Opening & closing resistance: Class 2 (10000 cycles)

#### Safety

Impact resistance: Class 3

Smoke & Heat Evacuation: NRWA

Bullet resistance: FB4

Operating Forces Class: Class 1

### Properties

#### Max. dimensions & weight

Max. height of vent: 2440 mm

Max. width of vent: 1440 mm

Max. weight of vent: 150 kg

#### Glazing

Rebate height: 20 mm

Glazing method: Dry glazing, Wet glazing

Glass thickness element: 20 -54.5 mm

Glass thickness vent: 20 -60 mm

#### Sightlines

Depth frame: 70 mm

Depth Vent: 88 mm

	inward	outward
Min. frame width	30 mm	-
Min. frame-vent width	62 mm	62 mm
Min. vent-vent width	102 mm	-