

Unico

Burglar resistance

FRAME YOUR IDEAS WITH **Forster Doors**

CONTACT INFO

Simpas Live Better
Location: Ampelia, Ioannina 45 500 Greece
Phone: +30 26510 92177 // +30 697 668 9259
www.simpasus.com

Technical Details

Thermal Insulation: $U_f = 1.3 \text{ W/m}^2\text{K}$

Air-Water-Wind: 4 / E900 / C3

Acoustics: $R_w(C;Ctrl) = 46\text{db}$

Burglar Resistance: RC2 –RC3

Min. frame width: Min. 50mm

Performance

Energy

Thermal insulation - U_f : $1.3 \text{ W/m}^2\text{K}$

Comfort

Air-Water-Wind: Class 4 (600Pa) -Class E900 (900Pa) -Class C3 (1200Pa)

Acoustics - $R_w(C;Ctr)$: 46 dB

Opening & closing resistance: Class 8 (1000000 cycles)

Safety

Burglar Resistance: RC2 –RC3

Impact resistance: Class 1

Operating Forces Class: Class 3

Properties

Max. dimensions & weight

Max. weight of vent: 410 kg

Free open width: 2740 mm

Free open height: 2990 mm

Glazing

Rebate height: 20 mm

Glazing method: Dry glazing, Wet glazing

Glass thickness element: 20 -54.5 mm

Glass thickness vent: 20 -54.5 mm

Sightlines

Depth frame: 70mm

Depth Vent: 70 mm

	inward	outward
Min. frame width	50 mm	-
Min. frame-vent width	110 mm	-
Min. vent-vent width	130 mm	-