

Presto 50

Fire resistance 60

FRAME YOUR IDEAS WITH **Forster Doors**

CONTACT INFO

Simpas Live Better
Location: Ampelia, Ioannina 45 500 Greece
Phone: +30 26510 92177 // +30 697 668 9259
www.simpasus.com

Technical Details

Air-Water-Wind: 4 / 8A / C4
Acoustics: $R_w(C;Ctrl) = 42dB$
Min. frame width: Min. 40mm

Performance

Comfort

Air-Water-Wind: Class 4 (600Pa) -Class 8A (450Pa) -Class C4 (1600Pa)
Acoustics - $R_w(C;Ctr)$: 42dB
Opening & closing resistance: Class 8 (1000000 cycles)

Safety

Impact resistance: Class 5
Fire resistance: E 60
Smoke resistance: S_1 / S_{200}

Properties

Max. dimensions & weight

Max. weight of vent: 410 kg
Free open width: 2180 mm
Free open height: 3000 mm

Glazing

Rebate height: 20 mm
Glazing method: Dry glazing, Wet glazing
Glass thickness element: 8 -39 mm
Glass thickness vent: 8 -39 mm

Sightlines

Depth frame: 50mm
Depth Vent: 50mm

	inward	outward
Min. frame width	40 mm	-
Min. frame-vent width	120 mm	-
Min. vent-vent width	150 mm	-