

Unico xs Standard

FRAME YOUR IDEAS WITH **ForsterWindows**

CONTACT INFO

Simpas Live Better
Location: Ampelia, Ioannina 45 500 Greece
Phone: +30 26510 92177 // +30 697 668 9259
www.simpasus.com

Technical Details

Thermal Insulation: $U_f = 1.9 \text{ W/m}^2\text{K}$

Acoustics: $R_w(C;Ctr) = 47\text{dB}$

Min. frame width: Min. 23mm

Performance

Energy

Thermal insulation - $U_f: 1.9 \text{ W/m}^2\text{K}$

Comfort

Air-Water-Wind: Class 4 (600Pa) -Class E1050 (1050Pa) -Class C5 (2000Pa)

Acoustics - $R_w(C;Ctr): 47 \text{ dB}$

Opening & closing resistance: Class 2 (10000 cycles)

Safety

Operating Forces Class: Class 1

Properties

Max. dimensions & weight

Max. height of vent: 2440 mm

Max. width of vent: 1440 mm

Max. weight of vent: 100 kg

Glazing

Rebate height: 15 mm

Glazing method: Dry glazing, Wet glazing

Glass thickness element: 20 -44 mm

Glass thickness vent: 20 -62 mm

Sightlines

Depth frame: 70 mm

Depth Vent: 88 mm

	inward	outward
Min. frame width	23 mm	-
Min. frame-vent width	55 mm	-
Min. vent-vent width	77 mm	-