

Unico xs

Burglar resistance

FRAME YOUR IDEAS WITH **ForsterWindows**

CONTACT INFO

Simpas Live Better
Location: Ampelia, Ioannina 45 500 Greece
Phone: +30 26510 92177 // +30 697 668 9259
www.simpasus.com

Technical Details

Thermal Insulation: $U_f = 1.9 \text{ W/m}^2\text{K}$

Acoustics: $R_w(C;Ctr) = 47\text{dB}$

Burglar Resistance: RC2

Min. frame width: Min. 23mm

Performance

Energy

Thermal insulation - U_f : $1.9 \text{ W/m}^2\text{K}$

Comfort

Air-Water-Wind: Class 4 (600Pa) -Class E1050 (1050Pa) -Class C5 (2000Pa)

Acoustics - $R_w(C;Ctr)$: 47 dB

Opening & closing resistance: Class 2 (10000 cycles)

Safety

Burglar resistance: RC2

Operating Forces Class: Class 1

Properties

Max. dimensions & weight

Max. height of vent: 2440 mm

Max. width of vent: 1440 mm

Max. weight of vent: 100 kg

Glazing

Rebate height: 15 mm

Glazing method: Wet glazing

Glass thickness element: 20 -42mm

Glass thickness vent: 21 -60 mm

Sightlines

Depth frame: 70 mm

Depth Vent: 88 mm

| | inward | outward |
|-----------------------|--------|---------|
| Min. frame width | 23 mm | - |
| Min. frame-vent width | 55 mm | - |
| Min. vent-vent width | 77 mm | - |